

MSA Permanent Instrument Accessories

Ti Techingenium

Distribuidores autorizados para Uruguay
 Venta - Ingeniería - Instalación - Mantenimiento
 Francisco Soca 1531
 Teléfono: +598 2 707 48 01
 Montevideo Uruguay
 Mail: info@techingenium.com.uy
 www.techingenium.com.uy




MSA supplies a full line of accessories for use with our permanent instruments. Simply select those that meet your need to create your own individualized monitoring solution.



Ultima® X Gas Monitor Accessories:


Pushbutton

To acknowledge an event or initialize calibration.



HART port

Intrinsically safe connection for a HART communicator.



Ultima XI calibration cap

A snap-on cap that enables XI calibration.



Calibrator

Offers the industry's simplest method of calibration. An easy-to-use, three-button device allows calibration and address change of the Ultima X Gas Monitor.



Sensor flow cap

Provides a regulated amount of flow during calibration.



Controller


Provides complete access to all advanced features of the Ultima X Gas Monitor through its full-function keypad. The controller is used to set the real time clock, set alarm levels, change span-gas values, display date of last calibration, display minimum, maximum and average gas values, change address and set future calibration time/date in addition to providing basic calibration functions. It is completely password-protected.



Power supplies

External power supplies enable remote powering of sensors. Internal power supply options are also available. One remote power supply module can power:

- ★ Up to 5 electrochemical or oxygen sensors
- ★ Up to 3 combustible sensors



MSA
The Safety Company

Ultima X accessories (continued):

Duct mount kits

Allow the user to monitor air within ductwork. A quick-disconnect fitting enables the calibration gas to reach the sensor without having to remove the duct-mounted sensor.



Sampling pump modules

Are available to bring a remote sample to a sensor. The sampling modules are available in GP (General Purpose) and XP (Explosion Proof) versions of aspirated and pumped modules.



Other accessories:

Mounting brackets

For mounting the monitor on a wall.



Stainless steel tags

For customer-specific naming requirements.



Strobes & horns

Offer prominent visual and audible indications of system alerts.



Remote display modules

Provide the ability to remotely view the status of a gas monitor.



Filters

For sample conditioning the filters remove particulate and liquids from the sample stream.



For more information on accessories or other MSA gas detection solutions, visit www.MSANet.com or contact Sales at 1-800-MSA-INST.

Note: This Bulletin contains only a general description of the products shown. While uses and performance capabilities are described, under no circumstances shall the products be used by untrained or unqualified individuals and not until the product instructions including any warnings or cautions provided have been thoroughly read and understood. Only they contain the complete and detailed information concerning proper use and care of these products.



ID 0703-01-MC /May 2008
© MSA 2008 Printed in U.S.A.

Corporate Headquarters
P.O. Box 426, Pittsburgh, PA 15230 USA
Phone 412-967-3000
www.MSANet.com

U.S. Customer Service Center
Phone 1-800-MSA-INST
Fax 1-724-776-3280

MSA Canada
Phone 1-800-672-2222
Fax 1-800-967-0398

MSA Mexico
Phone (52) 55 2122 5770
Fax (52) 55 5359 4330

MSA International
Phone 412-967-3354
FAX 412-967-3451

MSA
The Safety Company