



MSA PrimaX[®] IR Gas Monitor

Reliable Performance in Extreme Conditions

MSA PrimaX IR Gas Monitor

Every feature of the SIL 2-certified PrimaX IR Gas Monitor is designed with reliability in mind to withstand the most challenging environmental conditions throughout the product's life. MSA's **PrimaX IR Gas Monitor** offers LEL (Lower Explosive Limit) combustible gas detection through a patent-pending PrimaX Gas Monitor **IR dual-source** design. A redundant IR source provides reliability and uninterrupted monitoring should a source failure occur. Furthermore, the possibility of obscurations due to rain, fog, dirt, dust, and other environmental conditions is minimized due to dual-source design. In addition, optics are optimized for maximum signal, resulting in a product of extraordinary stability.



“The PrimaX IR Gas Monitor provides reliable operation, just like I have come to expect from MSA.”

– TB, Engineer



Installation

The PrimaX IR Gas Monitor is designed for quick and easy installation. Stainless steel and aluminum junction boxes can be ordered pre-installed for further ease of installation and wiring. A unique environmental guard with patent-pending clamshell design provides convenient installation in tight locations.



Calibration-Cap Method

Users may choose the most suitable calibration method for their applications. A calibration cap is placed on the unit to provide one-person calibration. Calibration cap icon-driven user interface guides users through the calibration process.

Calibration - HART Remote Method

HART (Highway Addressable Remote Transducer) output provides remote calibration capability. A HART junction box is offered for local calibration in classified areas; HART software is available to initiate calibration from remote locations.

Maintenance

The PrimaX IR Gas Monitor is designed to minimize maintenance costs without replacement of internal components. The PrimaX IR Gas Monitor dual-source design reduces potential system faults due to obscurations caused by rain, fog, dirt, etc. This monitor provides maintenance alerts as well as other fault conditions over 4-20mA and HART outputs.

Specifications

Description	Specification
Gas Types and Ranges	Hydrocarbon gases & vapors; 0-100% LEL
Temperature Range	-50°C to 75°C (-58°F to 167°F)
Stability	±2% full-scale/year
Repeatability	±1% full-scale
Accuracy	±2% full-scale (≤50% LEL) ±5% full-scale (>50% LEL)
Response Times without environmental guard with environmental guard	T90 <5 sec. Tested as per procedure in IEC 60079-29-1 For 50% LEL, 50% response in <5s, 90% response in <10s
Humidity	0%-95% RH, non-condensing
Sensor Warranty	10 years for IR source, 3-year full product
Power Input	18-32 VDC, 5 watts (-40°C to 75°C) (-40°F to 167°F)
Current Draw	150mA RMS average @ 24VDC
Wiring Requirements	3-wire, 2.0 mm max (14AWG)
Signal Output	4-20mA 3-wire current source with HART protocol
Physical Weight Dimensions	316 stainless steel 4.5 lbs. (2.0 kg) 3.5" dia. x 8" long (89 x 203mm)
Approval Ratings	US and Canada cFMus Class I, Div. 1, Groups A,B, C, & D Class II, Div. 1, Groups E, F, & G Class III ANSI/ISA 12.13.01 CSA C22.2 No. 152 Combustible Gas Performance International CE EMC Directive: 2004/108/EC CE ATEX Directive: 94/9/EC II 2G Ex d IIc T4 IEC China Ex/CMC/CCCF Russia Ex/ GOST R (Tamb -50°C to 75°C) (-58°F to 167°F)
Ingress Protection	IP67
HART	HART 7.0 compatible
Safety Integrity Level	SIL 2

Features & Benefits

- Patented dual-source design provides redundancy and reliable, uninterrupted performance
- Patent-pending environmental guard sensor housing for fast, efficient response time
- Heated optics prevent condensation buildup
- 4-20mA analog output
- User-friendly setup, calibration, diagnostics, and maintenance via HART digital communication
- One-person calibration is easily performed using calibration cap
- Easy connection using aluminium or stainless steel junction box
- SIL 2-certification provides safety system integration capability
- 316 stainless steel, IP67-rated, rugged housing protects unit from environmental extremes
- Factory-calibrated for fast commissioning
- Heater element enables operation to -50°C (-58°F)



Applications

- OGP including platforms, refineries, drilling rigs, and compressor stations
- Chemical plants
- Fuel-loading and storage facilities
- Wastewater
- Various industrial applications

Options & Accessories



Calibration cap




Stainless steel junction box



HART junction box



Duct-mount kit



Sun shield



Insect guard



Flow cap



Environmental guard tether



Note: This bulletin contains only a general description of the products shown. While uses and performance capabilities are described, under no circumstances shall the products be used by untrained or unqualified individuals and not until the product instructions including any warnings or cautions provided have been thoroughly read and understood. Only they contain the complete and detailed information concerning proper use and care of these products.



MSA – The Safety Company
1000 Cranberry Woods Drive
Cranberry Township, PA 16066 USA
Phone 724-776-8600
www.MSAafety.com

U.S. Customer Service Center
Phone 1-800-MSA-INST
Fax 1-800-967-0398

MSA Canada
Phone 1-800-MSA-INST
Fax 1-800-967-0398

MSA Mexico
Phone 01-800-672-7222
Fax 52-44 2227 3943

MSA International
Phone 724-776-8626
Toll Free 1-800-672-7777
FAX 724-741-1553
Email msa.international@MSAafety.com

ID 07-1807-MC / March 2015

© MSA 2015 Printed in U.S.A.

MSA
The Safety Company