

VeriSens[®] vision sensors

Image-based quality control – easy and intuitive.



Eyeing
your
quality.

Simply focused on the essentials.

Baumer is a global leader in sensor solutions for factory and process automation. More than 2,700 employees in 39 subsidiaries in 19 countries are at your service across the globe.

Baumer ranks with its powerful vision sensors among the world's most successful suppliers in this product category. Our customers profit from a structured product portfolio with high functionality and innovative features.

Everything we do is governed by our mission to continuously improve our products and shape technological developments. At the same time we focus on high performance, outstanding quality and simple operation – giving you more time for solving your application needs.

Where standard products come to their limits, we develop market-oriented, customized components in close cooperation with our customers. The result: Your decisive competitive edge.



The right vision sensor for your application.

Are you looking for a sensor where maximum functional and operational flexibility go together with easy process integration? *VeriSens*[®] vision sensors offer all these benefits – and still many more.

What exactly is a *VeriSens*[®] vision sensor?

VeriSens[®] is a complete image processing system in the shape of a sensor. An image sensor, illumination (or illumination connection), optics (also interchangeable lenses), hardware / software, as well as Ethernet and digital interfaces, e.g. for PLC connection, are integrated in a compact, industry-suited housing. After typical one-time configuration on PC, a vision sensor is ready to perform a specific task like a conventional sensor.

VeriSens[®] vision sensors solve inspection tasks and can perform up to 32 feature checks simultaneously:

- Presence and completeness checks
- Determination or inspection of object position and orientation
- Reading and verifying human-readable imprints (OCR / OCV)
- Reading and checking matrix codes and barcodes including GS1 codes

How does a *VeriSens*[®] vision sensor work?

VeriSens[®] acquires images, evaluates them and communicates the results to the system control or to individual components in your system. Initial configuration on PC allows you entry of image acquisition parameters, selecting tools for feature checks and setup of the required interfaces.

Where does *VeriSens*[®] make the most sense?

VeriSens[®] vision sensors tap their full potential of efficiency wherever various features must be checked in parallel or part locations vary, tasks which usually are only mastered by sophisticated sensor technology. This also includes applications where a visual inspection is advisable and/or contactless checks are required.

An intelligent sensor like *VeriSens*[®] is also the optimum component for checking (even different) batches in the line or communicating collected data.

VeriSens[®] vision sensors operate extremely efficient – depending on the scope of feature checking, more than 8,000 inspections per minute can be performed.

VeriSens[®] vision sensors at a glance

- Wide variety of feature checks with one single sensor
- Easy configuration within a few minutes
- Compact, industry-suited metal housing with protection class IP 67 or IP 69K
- Intuitive and unified configuration software
- Versatile connection options via digital I/O and Industrial Ethernet



VeriSens® – tried and tested in many industries.

We have earned a reputation supplying the automotive, food and beverage as well as packaging industry where we have acquired many years of expertise. We are also close to the medical and pharmaceutical sector by supplying sensor technology to perform inspection tasks and to provide vital findings.

Every industry has its particular needs. We would like to give you a brief overview of how and where our detection and inspection technology is applied.




Food and beverage industry

- Checking best-before dates
- Presence and position of straws on primary packaging
- Position of safety closures
- and many more

Example:

Inspection of best-before dates



OK



NOK





Packaging industry


- Cap monitoring
- Foil wrapping seams
- Label inspection (logo, text, code, product content, etc.)
- and many more

Example:

Inspection of forward cap alignment



OK



NOK





Automotive industry/electronics


- Assembly and surface mounting monitoring
- Presence and alignment check of pins
- Detection of overmolding, injection molding errors, scratches, etc.
- and many more

Example:

Inspection of fuse type (color) position



OK




NOK



Assembly/handling

- Position detection for pick & place
- Presence check and position monitoring of components
- Position of protective caps or plugs
- and many more

Example: Position detection of blanked parts for pick & place



OK



NOK

Inspired by nature.

Flexibility

We recognize objects in their entirety and this way can easily determine their position.

Object recognition

We can identify objects even in weak light – namely, by their contour.

Clearly focused

We can focus on specific details.



Robust

Our sensitive eye lens is protected by the flexible eyelid.

Communicative

Our eyes are linked to the high-speed network of our nervous system.

A clever mind on top

The eye requires intelligence.

Light conditions

Using artificial illuminations we can see even in weak light.

Our technology as evolution.

Flexibility

No matter how something is positioned on the conveyor belt – the integrated 360° *FEXLoc*® part recognition always keeps *VeriSens*® feature checks on track.

Object recognition

VeriSens® features a contour-based mode of operation – in real time calculated by the patented Baumer *FEX*® image processor.

Clearly focused

VeriSens® offers free choice of lenses to ensure optimum object focusing.



Robust

Every *VeriSens*® provides at least IP 67 protection. Industry-suited metal housing and modular tube system protect the entire vision sensor, even including the interchangeable lens.

Clever technology combined

VeriSens® is a perfectly harmonized system to see, decide, communicate – and even to learn new things.

Communicative

VeriSens® provides results over Ethernet, Industrial Ethernet or digital I/Os and even controls Universal Robots (UR).

Light conditions


VeriSens® features integrated machine vision illumination. Besides powering external illumination, the models of the XC series are the only vision sensors with fully integrated flash controller to multiply brightness.

VeriSens® – even faster and more objective than nature.

Do you want to benefit from the flexibility and versatility of image-based product verification as well? As a compact image processing system in the shape of a sensor, *VeriSens*® is an ideal component which comes with all the necessary hardware and software and is also intuitively configurable using a PC.


What makes *VeriSens*[®] so special for our customers?

- Patented Baumer *FEX*[®] image processor – inspired by nature
Any process deviations, such as varying light intensity, demanding object surfaces or ambient background influence quality in image processing. *VeriSens*[®] acts like human beings who can still recognize trees and houses clearly by their contours even in dismal weather: The patented *FEX*[®] image processor calculates contours in real time where others discern only shades of gray. Contour-based image processing works reliably and quickly – even in less stable ambient light conditions.



Visualization of the detected object by conventional image processing (bottom) and contour-based technology using Baumer *FEX*[®] image processor (top)

- *FEXLoc*[®] part location – to simplify the machine design
The location of parts during feeding does not matter to *VeriSens*[®]. Reliable 360° part recognition enables virtual object alignment to check the correct positions. This means that mechanical part alignment is no longer necessary. All XF, XC, and CS series models are equipped with integrated *FEXLoc*[®] part location.




Virtual object alignment using *FEXLoc*[®]
left: object contours
right: object turned in front of severe background structures



See the right colors even faster – with *ColorFEX*[®] in 3D

ColorFEX[®] is the unique, intelligent 3D color assistant for quick and intuitive setup of colors and their differentiation. Object colors and their shades are automatically identified and visualized in 3D. This allows for very easy and self-explaining setup of reliable color inspections.



TUTORIAL

Easy to use.



- **SmartGrid** – the intelligent calibration target

SmartGrid (patent-pending) provides four benefits: Supporting automated teach-in for image distortion correction in real time, it allows for precise object and dimensional checks even when *VeriSens*[®] is installed in inclined position. When converting to world coordinates, *VeriSens*[®] is receiving scaling specifications via *SmartGrid* (optionally with Z calibration). *SmartGrid* is the basis for automated coordinate alignment by *VeriSens*[®] when attached to Universal Robots (UR) to determine object positions.




Image distortion correction (right: corrected)


- **Universal Robots (UR) control** – easier than ever before

VeriSens[®] controls Universal Robots (UR) after just a few minutes of setup. Automated coordinate alignment via *SmartGrid* replaces the conventional manual “hand-eye” procedure. *VeriSens*[®] *URCap* is the user-friendly UR “app” and allows for easy vision sensor installation and integration into the program flow. UR programming utilizes only two additional nodes (commands) for image processing and thus remains as easy as ever: from tracking several objects including free space checks to identifying free storage space on to quality inspections and object identification – there are virtually no limits for applications.




- **Industry-suited design with IP 67 resp. IP 69K protection**

VeriSens[®] vision sensors come in robust aluminium respectively stainless steel housing that is up to harsh industrial environments. The patented modular tube system for the models with C-mount interface provides optimum protection for interchangeable lenses. Variable intermediate rings allow fast and economical adaptation to longer lenses – retrospectively as well.



Easy to configure.



Unified configuration software and integrated web interface.

Thanks to *VeriSens® Application Suite*, the cross-series unified configuration software available in 9 languages, your vision sensor is configured in just four easy-to-understand steps. Even for beginners the first job configuration will take only a few minutes, saving valuable time on the project.

Software includes simulators for every device – any conventional digital camera or smartphone as image source will do.

The simulators allow you to test feature checks offline prior to product purchase. An installation is not required – no need for administrator privileges.

A configurable human-machine interface is already integrated within the device for customers who want to configure *VeriSens®* also during the production process.

The *VeriSens® Application Suite* needs only a few clicks to set web interface options (functionalities, user groups, design) and therefore will be operational in just a few minutes. Security is provided by the encrypted HTTPS connection (device dependent). The *MultiViewer* feature enables selection of up to 16 *VeriSens®* vision sensors for view a standard web browser – therefore you will always be able to keep an eye on the entire production line.



Download and test free of charge
VeriSens® Application Suite
www.baumer.com/vs-sw



VeriSens® software at a glance

VeriSens® Application Suite for configuration and offline simulation

- Intuitive to use, even for non-expert users
- 4 steps to solve your inspection task
- Optionally with pop-up context help



TUTORIAL

VeriSens® web interface for visualization and monitoring in operation


- Visualization using the existing web browser, no plug-ins required
- Functionalities and design configured within few minutes
- Optimized for touch screen operation, optional user levels




TUTORIAL

Absolutely powerful.






VeriSens® Application Suite




VeriSens® web interface



VeriSens® MultiViewer

Absolutely ingenious.





XF series: All aboard!

XF stands for “eXtended Functionality” – the series includes everything required to immediately enter the world of image processing. The versatile scope of functionalities ensures maximum flexibility of up to 22 feature checks and makes sure the right image tool is always available. A single sensor will suffice for simultaneously checking object properties and positions as well as reading text (OCR/OCV) and 1D/2D codes. All XF series models feature robust 360° part location by *FEXLoc*® for reliable part recognition.

The XF models integrate LED illumination in white or infrared. Infrared with integrated daylight filter provides several application benefits such as highlighting particular object features and minimizing ambient light effects. Furthermore, nobody working nearby will be bothered by flashing *VeriSens*® illumination.

XF series

- Image evaluation: monochrome or color
- Includes all *VeriSens*® feature checks (up to 22)
- Integrated optics: 8 | 10 | 12 | 16 mm
- Integrated illumination, white or infrared
- Housing: aluminum (IP 67) or stainless steel (IP 69K)

- **Models XF700 /XF800 /XF900**
Latest hardware generation to boost productivity, with enhanced identification algorithms (XF800 /XF900), integrated real-time distortion correction and Industrial Ethernet (PROFINET and EtherNet/IP™)
- **Models XF700C /XF800C (color)**
Latest hardware generation with *ColorFEX*® color assistant for convenient and reliable color setup and integrated Industrial Ethernet (PROFINET and EtherNet/IP™)
- **Models XF800 /XF900**
Identification functions additionally: 1D / 2D code identification, reading of plain text (OCR) without requiring previous font training, print quality evaluation (OCV)
- **Models XF900**
The robot expert that integrates into the program flow of Universal Robots (UR) with the help of *VeriSens*® *URCap* – for image-based object tracking and robot-supported quality control, optional Z calibration for coordinate scaling in space





XC series: Maximum flexibility.

XC is an abbreviation of “eXtended Functionality with C-mount” – the series for maximum functionality and versatility. Advanced users benefit from up to 22 feature checks and the freedom to choose lens and illumination.

External illumination is supplied by the integrated *VeriFlash*® flash controller powering at the required pulse up to 48V and 4A. *ColorFEX*®, the intelligent and multiple award-winning 3D color assistant, enables intuitive and quick color setup in 3D. The patented and modular *VeriSens*® XC Tube System is the optimum protection for interchangeable lenses and can be configured to match the individual size of the lens.

■ Models XC700 / XC800 / XC900

Latest hardware generation to boost productivity, with enhanced identification algorithms (XC800 / XC900), integrated real-time distortion correction and Industrial Ethernet (PROFINET and EtherNet/IP™), XC800 / XC900 with additional identification functions: 1D / 2D code identification, reading of plain text (OCR) without requiring previous font training, printing quality evaluation (OCV), XC900: The robot expert that integrates into the program flow of Universal Robots (UR) with the help of *VeriSens*® *URCap* – for image-based object tracking and robot-supported quality control, optional Z calibration for coordinate scaling in space

■ Models XC700C / XC800C (color)

Latest hardware generation with *ColorFEX*® color assistant for convenient and reliable color setup, XC800C with additional identification functions

XC series

- Image evaluation: monochrome or color
- Includes all *VeriSens*® feature checks (up to 22)
- C-mount and free choice of lenses
- *VeriFlash*® flash controller
- Industry-suited aluminum housing (IP 67)





CS/ID series: The experts.

The VeriSens® sensor functionalities of the CS and ID series focus on core application tasks making them the ideal entry-level product for image-based object inspection.

The CS series (“Check & Sort”) provides every tool required for checking and sorting applications:

- **Model CS100**
Either with white or infrared illumination – particularly easy-to-use vision sensors designed for product inspection with immediate results output via digital I/Os

The ID series (“IDentification”) features both reliable text readers and code readers:

- **Model ID510 (text and code reader)**
Latest hardware generation to double productivity, integrated Industrial Ethernet (PROFINET and EtherNet/IP™), enhanced identification algorithms, in addition: reading of plain text (OCR) without requiring previous font training, print quality evaluation (OCV)
- **Model ID100 (code reader)**
Reads barcodes and matrix codes (1D/2D codes including GS1) with quality evaluation

CS/ID series







- Image evaluation: monochrome
- Selected VeriSens® feature checks (up to 6)
- Integrated optics, 10 mm, 12 mm or 16 mm
- Integrated illumination, white or infrared
- Housing: aluminum (IP 67)



VeriSens[®] vision sensors product overview

Additional devices (including IP 69K):
www.baumer.com/verisens

| | | | | | | | | | | | | | | | | | | | | | | | | | |
|---|--|----------------------|-----------------------------|---------------------------------|------------------|---------------------------|-----------------|----------------------------------|---------------------------|----------------------------|------------------|--------------------|-----------------------|---|------|-------------------|--------------------|--------------------|--------------------|-------------------|-----------|---|--------------------|---------------------------|------------------|
| Type key (e.g.): VS XF 800 M 03 W 12 I P | | Series (XF/XC/CS/ID) | Model with protection class | IP 67 (100/200/510/700/800/900) | IP 69K (105/205) | Sensor (Monochrome/Color) | Resolution [px] | 752/640 × 480 (VGA, 1/3" / 1/4") | 1280 × 960 (1.2 MP, 1/3") | 1600 × 1200 (2 MP, 1/1.8") | LED illumination | White (integrated) | Infrared (integrated) | VeriFlash [®] flash controller | Lens | 8 mm (integrated) | 10 mm (integrated) | 12 mm (integrated) | 16 mm (integrated) | C-mount interface | Interface | Ethernet (TCP/UDP), Industrial Ethernet ¹⁾ | Ethernet (TCP/UDP) | Ethernet (TCP/UDP), RS485 | Output (PNP/NPN) |
| | | XF | | 800 | M | | 03 | 12 | 20 | | W | I | X | | 8 | 10 | 12 | 16 | 00 | | I | E | R | P | |

| Article No. | Type name | | | | | | | | | | | | | | | | | | | | | | | |
|---|---------------------------|----|---|---|---|--|---|--|---|--|---|--|---|--|---|--|---|--|---|--|---|--|-----------------|---|
|  | 11700462 VS XF700M03W08IP | XF | ■ | M | ■ | | ■ | | ■ | | ■ | | ■ | | ■ | | ■ | | ■ | | ■ | | | P |
| | 11173091 VS XF700M03W12IP | | ■ | | ■ | | ■ | | ■ | | ■ | | ■ | | ■ | | ■ | | ■ | | ■ | | | |
| | 11173090 VS XF700M03W16IP | | ■ | | ■ | | ■ | | ■ | | ■ | | ■ | | ■ | | ■ | | ■ | | ■ | | | |
| | 11700463 VS XF700M03I08IP | | ■ | | ■ | | ■ | | ■ | | ■ | | ■ | | ■ | | ■ | | ■ | | ■ | | | |
| | 11173089 VS XF700M03I12IP | | ■ | | ■ | | ■ | | ■ | | ■ | | ■ | | ■ | | ■ | | ■ | | ■ | | | |
| | 11173088 VS XF700M03I16IP | | ■ | | ■ | | ■ | | ■ | | ■ | | ■ | | ■ | | ■ | | ■ | | ■ | | | |
| | 11210957 VS XF800M03W08IP | | ■ | | ■ | | ■ | | ■ | | ■ | | ■ | | ■ | | ■ | | ■ | | ■ | | | |
| | 11162177 VS XF800M03W12IP | | ■ | | ■ | | ■ | | ■ | | ■ | | ■ | | ■ | | ■ | | ■ | | ■ | | | |
| | 11162175 VS XF800M03W16IP | | ■ | | ■ | | ■ | | ■ | | ■ | | ■ | | ■ | | ■ | | ■ | | ■ | | | |
| | 11700461 VS XF800M03I08IP | | ■ | | ■ | | ■ | | ■ | | ■ | | ■ | | ■ | | ■ | | ■ | | ■ | | | |
| | 11173087 VS XF800M03I12IP | | ■ | | ■ | | ■ | | ■ | | ■ | | ■ | | ■ | | ■ | | ■ | | ■ | | | |
| | 11173086 VS XF800M03I16IP | | ■ | | ■ | | ■ | | ■ | | ■ | | ■ | | ■ | | ■ | | ■ | | ■ | | | |
| | 11700457 VS XF900M03W08IP | | ■ | | ■ | | ■ | | ■ | | ■ | | ■ | | ■ | | ■ | | ■ | | ■ | | | |
| | 11700458 VS XF900M03W12IP | | ■ | | ■ | | ■ | | ■ | | ■ | | ■ | | ■ | | ■ | | ■ | | ■ | | | |
| | 11700460 VS XF900M03I08IP | | ■ | | ■ | | ■ | | ■ | | ■ | | ■ | | ■ | | ■ | | ■ | | ■ | | | |
| | 11700459 VS XF900M03I12IP | | ■ | | ■ | | ■ | | ■ | | ■ | | ■ | | ■ | | ■ | | ■ | | ■ | | | |
|  | 11197478 VS XF700C03W12IP | XF | ■ | C | ■ | | ■ | | ■ | | ■ | | ■ | | ■ | | ■ | | ■ | | ■ | | | P |
| | 11197479 VS XF700C03W16IP | | ■ | | ■ | | ■ | | ■ | | ■ | | ■ | | ■ | | ■ | | ■ | | ■ | | | |
| | 11210959 VS XF800C03W08IP | | ■ | | ■ | | ■ | | ■ | | ■ | | ■ | | ■ | | ■ | | ■ | | ■ | | | |
| | 11199868 VS XF800C03W12IP | | ■ | | ■ | | ■ | | ■ | | ■ | | ■ | | ■ | | ■ | | ■ | | ■ | | | |
| | 11199869 VS XF800C03W16IP | | ■ | | ■ | | ■ | | ■ | | ■ | | ■ | | ■ | | ■ | | ■ | | ■ | | | |
|  | 11173085 VS XC700M03X00IP | XC | ■ | M | ■ | | ■ | | ■ | | ■ | | ■ | | ■ | | ■ | | ■ | | ■ | | | P |
| | 11173084 VS XC700M12X00IP | | ■ | | ■ | | ■ | | ■ | | ■ | | ■ | | ■ | | ■ | | ■ | | ■ | | | |
| | 11173083 VS XC700M20X00IP | | ■ | | ■ | | ■ | | ■ | | ■ | | ■ | | ■ | | ■ | | ■ | | ■ | | | |
| | 11166806 VS XC800M03X00IP | | ■ | | ■ | | ■ | | ■ | | ■ | | ■ | | ■ | | ■ | | ■ | | ■ | | | |
| | 11166807 VS XC800M12X00IP | | ■ | | ■ | | ■ | | ■ | | ■ | | ■ | | ■ | | ■ | | ■ | | ■ | | | |
| | 11166808 VS XC800M20X00IP | | ■ | | ■ | | ■ | | ■ | | ■ | | ■ | | ■ | | ■ | | ■ | | ■ | | | |
| | 11700454 VS XC900M03X00IP | | ■ | | ■ | | ■ | | ■ | | ■ | | ■ | | ■ | | ■ | | ■ | | ■ | | | |
| | 11700456 VS XC900M12X00IP | | ■ | | ■ | | ■ | | ■ | | ■ | | ■ | | ■ | | ■ | | ■ | | ■ | | | |
| | 11700455 VS XC900M20X00IP | | ■ | | ■ | | ■ | | ■ | | ■ | | ■ | | ■ | | ■ | | ■ | | ■ | | | |
|  | 11181282 VS XC700C03X00IP | XC | ■ | C | ■ | | ■ | | ■ | | ■ | | ■ | | ■ | | ■ | | ■ | | ■ | | | P |
| | 11181283 VS XC700C12X00IP | | ■ | | ■ | | ■ | | ■ | | ■ | | ■ | | ■ | | ■ | | ■ | | ■ | | | |
| | 11166809 VS XC800C03X00IP | | ■ | | ■ | | ■ | | ■ | | ■ | | ■ | | ■ | | ■ | | ■ | | ■ | | | |
| | 11180704 VS XC800C12X00IP | | ■ | | ■ | | ■ | | ■ | | ■ | | ■ | | ■ | | ■ | | ■ | | ■ | | | |
|  | 11048500 VS CS100M03W10EP | CS | ■ | M | ■ | | ■ | | ■ | | ■ | | ■ | | ■ | | ■ | | ■ | | ■ | | □ ²⁾ | P |
| | 11076261 VS CS100M03W16EP | | ■ | | ■ | | ■ | | ■ | | ■ | | ■ | | ■ | | ■ | | ■ | | ■ | | □ ²⁾ | |
| | 11089900 VS CS100M03I10EP | | ■ | | ■ | | ■ | | ■ | | ■ | | ■ | | ■ | | ■ | | ■ | | ■ | | □ ²⁾ | |
| | 11093026 VS CS100M03I16EP | | ■ | | ■ | | ■ | | ■ | | ■ | | ■ | | ■ | | ■ | | ■ | | ■ | | □ ²⁾ | |
|  | 11048489 VS ID100M03W10RP | ID | ■ | M | ■ | | ■ | | ■ | | ■ | | ■ | | ■ | | ■ | | ■ | | ■ | | ■ | P |
| | 11076263 VS ID100M03W16RP | | ■ | | ■ | | ■ | | ■ | | ■ | | ■ | | ■ | | ■ | | ■ | | ■ | | ■ | |
| | 11173082 VS ID510M03W12IP | | ■ | | ■ | | ■ | | ■ | | ■ | | ■ | | ■ | | ■ | | ■ | | ■ | | ■ | |
| | 11173081 VS ID510M03I12IP | | ■ | | ■ | | ■ | | ■ | | ■ | | ■ | | ■ | | ■ | | ■ | | ■ | | ■ | |

¹⁾ PROFINET/Ethernet/IP™





²⁾ for configuration only

A question of light.

A decisive criterion for inspection stability in the application is the accentuation of differences in application-relevant features. Therefore illumination should be selected with utmost care in order to obtain optimum results. Basically, there is incident light,

dark field and back light. Colored illumination may cause strong contrast. Due to the topic's complexity, the following provides only a rough outline. The Baumer team will gladly be of help should you need more detailed support.


Illumination position

| Illumination type | Ideal for | Object |
|--|--|---|
| Incident light Homogenous illumination of rough and matte objects | Presence and position checks, imprint inspection (OCR/OCV), e. g. best-before date |  |
| Dome light Shadow-free illumination, suppression of surface irregularities and reflections | Inspection of severely glossy or mirroring objects, e. g. yogurt lids (seals) |  |
| Dark field light Highlighting any unevenness, contours, edges and defects | Surface inspection, e. g. scratches or engravings |  |
| Back light Inspected object illumination from below or behind delivers high-contrast shadow images | Contour-based inspection, e. g. accuracy of punched parts and mounting holes, measuring operations, presence checks of transparent packaging |  |

Colored illumination

Colored illumination may intensify or suppress defined colors also in monochrome imaging. The contrast created this way helps recognizing relevant features which is decisive for an application-specific and optimally matching solution.

For example, blue light cast on a multi-color surface will be reflected by the blue content only. The more blue content is in object, the more light is reflected and the brighter will appear the object. In an analog way, red content illuminated in blue appears extremely dark.



In a nutshell.

Why is external illumination so easy with *VeriSens*[®] vision sensors? Where integrated LED illumination does not provide the required results, *VeriSens*[®] XC series is the solution. Thanks to *VeriFlash*[®], these sensors feature integrated flash controller which is directly connected to the external illumination. Just install and configure during setup using *VeriSens*[®] Application Suite – and you are ready to start!

In addition to the previously mentioned types of illumination, you have also the option to connect *VeriSens*[®] to high-end LUMIMAX[®] Spot5W made by iim AG – which also works with the XF, CS and ID models.

Just attach LUMIMAX[®] Spot5W to *VeriSens*[®] at the required distance and inclination angle using the Industrial Light Fix Kit and connect with Y-cable.


VeriSens[®] illumination concept with LUMIMAX[®] Spot5W

A single illumination to match multiple applications

- Adjustable glass optics for spotlight or homogenous illumination field
- Illumination in different colors and with polarization filter
- Flexible fixation at the XC / XF / ID / CS series

Installation and connection

- Easy and space-saving installation
- Angular and position adjustments reproducible by the applied markings
- Y-cable for quick installation and flashing via *VeriSens*[®] Flash Sync signal



LUMIMAX[®] Spot5W



LUMIMAX[®] Spot5W adapter



Industrial Light Fix Kit



Y-cable

Technical data


| General data | XC series | | | XF series CS series ID series |
|--|---|--|-------------------------|---|
| Resolution | 640 × 480 px | 1280 × 960 px | 1600 × 1200 px | 752 × 480 px |
| Sensor | 1/4" CCD (monochrome, color) | 1/3" CCD (monochrome, color) | 1/1.8" CCD (monochrome) | 1/3" CMOS (monochrome, color) |
| LED illumination | Fully integrated VeriFlash® flash controller for external illumination | | | White (LED class: Risk group 1 low risk, EN 62471:2008) Infrared (860 nm) (LED class: free group risk-free, EN 62471:2008) |
| Lens | Interchangeable lens (C-mount) | | | f = 10 mm f = 8 / 12 mm f = 16 mm |
| Min. object distance | Depending on interchangeable lens | | | 50 mm 50 mm 70 mm 100 mm ¹⁾ |
| Max. object distance | Depending on interchangeable lens | | | ∞ 450 mm 300 mm |
| Speed | Max. inspections/s | Max. inspections/s | Max. inspections/s | Max. inspections/s |
| High-resolution mode | 118 (monochrome) 116 (color) | 32 (monochrome) 31 (color) | 21 (monochrome) | 50 (monochrome) 50 (color) |
| High-speed mode* (* limited resolution) | 144 (monochrome) | 54 (monochrome) | 35 (monochrome) | 100 (monochrome, XF series only) |
| Defect image memory | 32 | 8 | 4 | 32 |
| Number of jobs | Up to 255 on the device (can be exchanged via process interface) | | | |
| Features per job | 32 | | | |
| Electrical data | XC series | | | XF series CS series ID series |
| Power supply | === 24 V ± 25 % / Class 2 per NEC / Protection class III | | | |
| Power consumption | Typical 8 W, max. 42 W (with IO and illumination) | | | Typ. 8 W, max. 18 W (with illumination) |
| Inputs | 8 ... 30 V DC | | | |
| Outputs | PNP I _{peak} = 100 mA and I _{eff} = 50 mA | | | |
| Digital input | Trigger, Job selection, External teach-in, Encoders (CH-A, CH-B) 500 kHz | | | |
| Digital output | Pass/Fail 1-5 ²⁾ , Flash Sync, Alarm, Camera Ready, Output Enable | | | ¹⁾ XF/XC 700/800/900, ID510 only |
| Communication | Ethernet (10BASE-T / 100BASE-TX) | | | ²⁾ VSxxxxxxxxxRP: 1-3 |
| Initial setup | PROFINET (CC-A) ¹⁾ / Ethernet/IP ^{TM 1)} , TCP/UDP (Ethernet) ³⁾ , RS485 ⁴⁾ | | | ³⁾ except CS100 |
| Process interface | | | | ⁴⁾ VSxxxxxxxxxRP only |
| Integr. flash controller | XC series | | | XF series CS series ID series |
| Voltage (permanent) | === 12 V DC or === 24 V DC | | | – |
| Voltage (pulsed) | ┘ 24 V DC or ┘ 48 V DC | | | – |
| Current (permanent) | I _{max} = 800 mA at === 24 V DC | (+/- 10 %, at least +/- 100 mA, at 25 °C) | | – |
| Current (pulsed) | I _{max} = 4 A at ┘ 48 V DC | (+10/-20 %, at least +/- 100 mA, at 25 °C) | | – |
| Flash time | Max. 1 ms (Duty Cycle max. 1:10) | | | – |
| Operating conditions | XC series | | | XF series CS series ID series |
| Temperature | Operating temperature: +5 ... +50 °C @ measurement point, Storage temperature: -20 ... +70 °C | | | |
| Humidity | 0 ... 90 % (non-condensing) | | | |
| Protection class | IP 67 (XC series: with tube) | | | IP 67 |
| Vibration load | IEC 60068-2-6, IEC 60068-2-64 | | | |
| Mech. shock resistance | EN 60068-2-27 | | | |
| Mechanical data | XC series | | | XF series CS series ID series |
| Width × Height × Depth | 53 mm × 99.5 mm × 49.8 mm (without lens / tube) | | | 53 mm × 99.5 mm × 38 mm |
| Material | Housing: aluminum Cover glass tube: PMMA | | | Housing: aluminum Cover glass: PMMA ⁵⁾ |
| Weight (approx.) | 300 g (without lens / tube) | | | 250 g |
| Code types/OCR | Model: XC800/900 | | | Models: XF800/900 ID510 ID100 |
| Barcode ⁶⁾ | 2/5 Industrial, 2/5 Interleaved, Codabar, Code 39, Code 93, Code 128, PharmaCode EAN 8, EAN 13, UPC-A, UPC-E: Base code + variants Add-On 2, Add-On 5 GS1 DataBar (RSS): Limited, Expanded, Expanded Stacked GS1 DataBar (RSS-14): Omnidir, Truncated, Stacked, Stacked Omnidir GS1 128 | | | |
| Matrix code ⁶⁾ | DataMatrix (ECC 200), GS1-DataMatrix, QR, PDF417 | | | |
| Font ⁷⁾ | Many font styles (recommended: sans serif, proportional), Dot Matrix, Characters: A-Z a-z 0-9 + - . : / () | | | |

⁵⁾ for XF700, XF800/900, CS100, ID510 with infrared illumination: daylight filter 780 nm integrated

⁶⁾ incl. quality rating of all barcodes according to ISO/IEC 15416 as well as all matrix codes according to ISO/IEC 15415 or AIM DPM-1-2006


⁷⁾ XC800/900, XF800/900, ID510 only

Dimension drawing (XC series)




Dimensions in mm

Electrical connection ¹⁾ M12 / 12-pin, A-coded




| | |
|------------------------|---------------------------------|
| 1: Power (+18-30 V DC) | 7: OUT3 |
| 2: Ground | 8: IN3 |
| 3: IN1 (Trigger) | 9: OUT4 RS485+ ²⁾ |
| 4: OUT1 | 10: IN4 |
| 5: IN2 | 11: IN5 |
| 6: OUT2 | 12: OUT5 RS485- ²⁾ |

Electrical connection illumination ^{1,3)} M8 / 4-pin ⁴⁾



| |
|--|
| 1: +24 V or +48 V Flash |
| 2: +12 V or +24 V Flash |
| 3: Ground |
| 4: Flash Sync ⁵⁾ PNP 100 mA |

Ethernet connection ¹⁾ M12 / 4-pin



| |
|--------|
| 1: TD+ |
| 2: RD+ |
| 3: TD- |
| 4: RD- |

¹⁾ on device


²⁾ RS485: VSxxxxxxxxRP only

³⁾ XC series only



⁴⁾ voltage outputs configurable by software

⁵⁾ voltage according to power supply

Dimension drawing (XF/CS/ID series)



* working distances > 400 mm possible



Device dependent:




System design


Lab setup accessories (optional)

| | |
|----------|--|
| 11048083 | Connecting cables <i>VeriSens</i> [®] , adapter M12 / DC socket |
| 11079750 | Power supply 24 V / 1 A, international, DC plug |
| 11051407 | Laboratory stand, hinged bracket, mounting material |







Mounting accessories (optional)

| | | |
|----------|---|---|
| 11177010 | <i>VeriSens</i> [®] mounting adapter |  |
|----------|---|---|

Polarization filter (optional)

| | | |
|----------|--|---|
| 11161075 | ZVF-Filter Pol. <i>VeriSens</i> [®] ID / CS / XF (VSxxxxxxxWxxxx only) |  |
|----------|--|---|

Connecting cables⁴⁾ shielded, to free cable end

| | | |
|----------|------|---|
| 11201118 | 2 m |  |
| 11195097 | 5 m |  |
| 11195098 | 10 m |  |
| 11201128 | 2 m |  |
| 11195094 | 5 m |  |
| 11195095 | 10 m |  |

⁴⁾ suitable for robotics, UL approved







Lens accessories (optional)

| | |
|----------|--|
| 11088325 | XC Tube, M47, length 44 mm (scope of delivery <i>VeriSens</i> [®] XC) |
| 11115649 | XC Tube Module, M47, 6 mm |
| 11089149 | XC Tube Module, M47, 12 mm |
| 11010529 | Close-up ring set 6-part, 0.5 / 1 / 5 / 10 / 20 / 40 mm |
| 11092000 | Pentax [®] polarization filter, linear: filter thread 27 mm ¹⁾ |
| 11175428 | filter thread 30.5 mm ²⁾ |
| 11167713 | filter thread 40.5 mm ³⁾ |
| 11006551 | Pentax [®] color filter ¹⁾ (red), filter thread 27 mm |
| 11097573 | IR cut filter, C-mount, height 2.5 mm, screw-in tool |
| 11097576 | Daylight filter, C-mount, height 2.5 mm, screw-in tool |



Compatible to lenses:


- ¹⁾ Article No. 11150226 / 11150228 / 11003417
- ²⁾ Article No. 11008992 / 11150229 / 11150230 / 11003041
11175031 / 11175034 / 11175035 / 11175036
- ³⁾ Article No. 11150223 / 11002877

Ethernet cables shielded, to RJ-45 plug







| | | |
|------|----------|---|
| 2 m | 11048502 |  |
| 5 m | 10165276 |  |
| 10 m | 11051929 |  |
| 2 m | 11048592 |  |
| 5 m | 11048594 |  |
| 10 m | 11051950 |  |

Monitor (All-in-one PC, optional)

| | | |
|----------|---|---|
| 11122988 | ZVP-ALL_IN_ONE_PC.DE (10.4", 1024 × 768 px, Stylus) |  |
| 11093293 | ZVP-ALL_IN_ONE_PC.EN (10.4", 1024 × 768 px, Stylus) |  |









Illumination cables

| | | | |
|----------|--------|---|---|
| 11088882 | 1.5 m | Extension cable shielded, male conn. straight M8, to female conn. straight M8 ⁵⁾ |  |
| 11136134 | 0.3 m | Extension cable shielded, male conn. straight M8, to female conn. straight M8 ⁵⁾ |  |
| 11089179 | 0.3 m | Adapter cable, male connector straight M8, to JST SMP-03V (3-pin) ⁵⁾ |  |
| 11089178 | 0.3 m | Adapter cable, male connector straight M8, to JST SMP-02V (2-pin) ⁵⁾ |  |
| 10163693 | 2 m | Adapter cable, free cable end, to female connector straight M8 ⁵⁾ |  |
| 11175008 | 0.15 m | Adapter cable, ZVI-LUMIMAX [®] T1 at <i>VeriSens</i> [®] XF / XC / CS / ID series |  |

⁵⁾ *VeriSens*[®] XC series only

Set of mounting brackets

| | | | | |
|----------|-------------------------------------|--|---|---|
| 11092203 | VB Fix Kit FLDR-i90B, small (57 mm) | for LED ring light FLDR-i90B to <i>VeriSens</i> [®] XC series |  |  |
| 11092204 | VB Fix Kit FLDR-i90B, large (93 mm) | | | |
| 11136136 | VB Fix Kit RONDO-LX, small (57 mm) | for LED ring light ZVI-RONDOLX to <i>VeriSens</i> [®] XC series |  |  |
| 11136139 | VB Fix Kit RONDO-LX, large (93 mm) | | | |
| 11076264 | ZVI-VB Fix Kit Industrial Light | for illumination (e. g. Spot 5W) to <i>VeriSens</i> [®] XF / XC / CS / ID |  |  |
| 11175009 | ZVI-VB Fix Kit Adapter Spot5W | | | |

Interchangeable lenses (C-mount, VeriSens® XC series only)




| Article No. | Type name | Focal distance [mm] | Aperture speed range | Minimum distance [m] | Maximum lens length ¹⁾ [mm] | Filter thread [mm] | XC Tube Module ²⁾ (Art. Nr. 11089149) |
|-------------|---------------------------------|---------------------|----------------------|----------------------|--|--------------------|--|
| 11037579 | ZVL-FL-HC0416X-VG ³⁾ | 4.2 | F1.6 - C | 0.20 | 44 | – | 1 piece |
| 11008992 | ZVL-FL-HC0614-2M ³⁾ | 6 | F1.4 - 16.2 | 0.10 | 38 | 30.5 | 1 piece |
| 11150223 | ZVL-FL-CC0814A-2M | 8 | F1.4 - 16.2 | 0.10 | 37 | 40.5 | 1 piece |
| 11002877 | ZVL-FL-CC0815B-VG ³⁾ | 8.5 | F1.5 - C | 0.20 | 40 | 40.5 | 1 piece |
| 11150226 | ZVL-FL-CC1214A-2M | 12 | F1.4 - 16.2 | 0.10 | 46 | 27.0 | 1 piece |
| 11150228 | ZVL-FL-CC1614A-2M | 16 | F1.4 - 16.2 | 0.10 | 33 | 27.0 | – |
| 11150229 | ZVL-FL-CC2514A-2M | 25 | F1.4 - 16.2 | 0.10 | 38 | 30.5 | 1 piece |
| 11003417 | ZVL-FL-CC3516-2M | 35 | F1.6 - 16 | 0.40 | 36 | 27.0 | – |
| 11150230 | ZVL-FL-CC5024A-2M | 50 | F2.8 - 22.2 | 0.30 | 47 | 30.5 | 1 piece |
| 11003041 | ZVL-FL-CC7528-2M | 75 | F2.8 - 32 | 0.70 | 60 | 30.5 | 3 pcs |

¹⁾ measured from C-mount support (see XC series scale drawing)

²⁾ necessary with lens length > 36 mm

³⁾ only compatible to VeriSens® with 0.3 MP resolution (VS XCxxxx03xxxxx)

External illumination modules ³⁾

| Article No. | Type name | Product description | Cable [cm] | Illuminated area [mm] | Outer dimensions [mm] | Height [mm] |
|--|-----------------------------------|--------------------------------------|---|-----------------------|-----------------------|-------------|
| Cable with M8/4-pin connector ^{3,4)} | | |  | | | |
| 11085869 | FLDR-i90B-W | LED ring light, white | 30 | ∅ 87 | ∅ 93,5 | 24.6 |
| 11154321 | FLDR-i90B-SR24 | LED ring light, red 626 nm | 30 | ∅ 87 | ∅ 93,5 | 24.6 |
| 11090900 | FLDR-i90B-IR24 | LED ring light, IR 875 nm | 30 | ∅ 87 | ∅ 93,5 | 24.6 |
| 11086539 | FLDL-i150x15-W | LED bar light, white, diffuse | 100 | 148 × 15 | 158 × 17.5 | 20 |
| 11086540 | FFPR-i100-W | LED dark field light, white, diffuse | 30 | ∅ 94,6 | ∅ 100 | 40 |
| 11086541 | FLDM-i100-W | LED dome light, white | 30 | ∅ 80 | ∅ 130 | 61 |
| 11086536 | FLDL-TP-Si36-W | LED back light, white, diffuse | 100 | 36 × 36 | 47 × 47 | 15 |
| 11086538 | FLDL-TP-Si85x77-W | LED back light, white, diffuse | 100 | 85 × 77 | 95 × 95 | 15 |
| 11086537 | FLDL-TP-Si200x100-W | LED back light, white, diffuse | 100 | 200 × 100 | 228 × 116 | 23.5 |
| 11095910 | FLFL-Si60-IR24 | LED back light, IR 850 nm, diffuse | 100 | 60 × 60 | 94 × 94 | 10 |
| With M8/4-pin connector ^{3,5)} | | |  | | | |
| 11130179 | ZVI-RONDOLX_24VDC_weiss_120° | LED ring light, white, 120° | – | ∅ 67 | ∅ 101 | 24 |
| 11130176 | ZVI-RONDOLX_24VDC_IR850nm_50° | LED ring light, IR 850 nm, 50° | – | ∅ 67 | ∅ 101 | 24 |
| 11130150 | ZVI-RONDOLX_24VDC_IR850nm_120° | LED ring light, IR 850 nm, 120° | – | ∅ 67 | ∅ 101 | 24 |
| 11130185 | ZVI-TOPLINED1_24VDC_weiss_120° | LED bar light, white, 120° | – | 78 × 25 | 78 × 25 | 23 |
| 11130186 | ZVI-TOPLINED1_24VDC_SHweiss_120° | LED bar light, SH white, 120° | – | 78 × 25 | 78 × 25 | 23 |
| 11130187 | ZVI-TOPLINED1_24VDC_rot617nm_30° | LED bar light, red 617 nm, 30° | – | 78 × 25 | 78 × 25 | 23 |
| 11135012 | ZVI-TOPLIGHT80_24VDC_rot617nm_30° | LED incident light, red 617 nm, 30° | – | 87 × 87 | 87 × 87 | 20 |
| 11130183 | ZVI-ARCUSM_24VDC_weiss_120° | LED dark field light, white, diffuse | – | ∅ 68 | ∅ 120 | 9.5 |
| 11130181 | ZVI-HILIGHT80_24VDC_weiss | LED back light, white, diffuse | – | 78 × 78 | 87 × 87 | 20 |
| 11130182 | ZVI-HILIGHT120_24VDC_weiss | LED back light, white, diffuse | – | 118 × 118 | 127 × 127 | 20 |
| With M16/12-pin connector ⁶⁾ | | |  | | | |
| 11175031 | ZVI-LED Spot5WFL-W/SPS-220 | LED spot light, white | 15 | ∅ 30 | ∅ 36 | 75–92 |
| 11175034 | ZVI-LED Spot5WFL-R/SPS-220 | LED spot light, red | 15 | ∅ 30 | ∅ 36 | 75–92 |
| 11175035 | ZVI-LED Spot5WFL-IR850/SPS-220 | LED spot light, IR 850 nm | 15 | ∅ 30 | ∅ 36 | 75–92 |
| 11175036 | ZVI-LED Spot5WFL-B/SPS-220 | LED spot light, blue | 15 | ∅ 30 | ∅ 36 | 75–92 |

³⁾ VeriSens® XC series only

⁴⁾ supplier: Falcon Illumination MV GmbH & Co. KG

⁵⁾ supplier: Büchner Lichtsysteme GmbH

⁶⁾ supplier: iiM AG






















⁷⁾ connector directly on the device

Illumination accessories (optional)

| | | | | | |
|----------|-----------------------------------|----------|---|----------|---------------------------------|
| 11167410 | Polarization filter for FLDR-i90B | 11167411 | Support polarization filter for für FLDR-i90B | 11167413 | Diffusor A1421 for FLDR-i90B-DP |
|----------|-----------------------------------|----------|---|----------|---------------------------------|










VeriSens[®] feature checks: overview.

VeriSens[®] vision sensors provide 23 different feature checks. The device-specific feature set is fully included with the purchase. Up to 32 checks can be performed all at once – with a single image acquisition – for comprehensive and efficient quality control.
















| | | | Models | | | | | |
|---|--|---|--|-------------------------------------|-------------------------------------|-------------------------------------|-------------------------------------|-------|
| | | | XF700 / XC700 [®] | XF800 / XC800 [®] | XF900 / XC900 | CS100 | ID510 | ID100 |
| Part location | | | | | | | | |
|  | <p>Part location on contours (FEXLoc[®]) Determines the location and rotational position of a part based on its contours. All subsequent feature checks are aligned according to the determined position.</p> |  |  | 360° | 360° | 360° | 360° | |
|  | <p>Part location on edges (FEXLoc[®]) Determines the location and rotational position of a part from a single edge or two edges at right angles to each other. All subsequent feature checks are aligned according to the determined position.</p> |  |  | <input checked="" type="checkbox"/> | <input checked="" type="checkbox"/> | <input checked="" type="checkbox"/> | | |
|  | <p>Part location on circle (FEXLoc[®]) Determines the location and rotational position of circular parts. All subsequent feature checks are aligned according to the determined position.</p> |  |  | <input checked="" type="checkbox"/> | <input checked="" type="checkbox"/> | <input checked="" type="checkbox"/> | | |
|  | <p>Part location on text line Determines the location and rotational position of text within a working area. The text may change during this task. All subsequent feature checks are aligned according to the determined position.</p> |  |  | <input checked="" type="checkbox"/> | <input checked="" type="checkbox"/> | <input checked="" type="checkbox"/> | <input checked="" type="checkbox"/> | |
| Geometry | | | | | | | | |
|  | <p>Distance Determines the distance between two edges.</p> |  |  | <input checked="" type="checkbox"/> | <input checked="" type="checkbox"/> | <input checked="" type="checkbox"/> | <input checked="" type="checkbox"/> | |
|  | <p>Circle Determines the diameter, location and roundness in comparison to a reference circle.</p> |  |  | <input checked="" type="checkbox"/> | <input checked="" type="checkbox"/> | <input checked="" type="checkbox"/> | <input checked="" type="checkbox"/> | |
|  | <p>Angle Determines the angle between two edges.</p> |  |  | <input checked="" type="checkbox"/> | <input checked="" type="checkbox"/> | <input checked="" type="checkbox"/> | | |

| Models | XF700 / XC700 [®] | XF800 / XC800 [®] | XF900 / XC900 | CS100 | ID510 | ID100 |
|--------|----------------------------|----------------------------|---------------|-------|-------|-------|
|--------|----------------------------|----------------------------|---------------|-------|-------|-------|

Geometry

| | | | | | | | | | |
|---|---|---|--|---|---|---|--|--|--|
|  | <p>Count edges Determines the number of edges along a tracing ray.</p> |  |  | ■ | ■ | ■ | | | |
|  | <p>Point position Determines the coordinates of one point.</p> |  |  | ■ | ■ | ■ | | | |
|  | <p>Edge characteristics Compares the distances of edges along a tracing ray.</p> |  |  | ■ | ■ | ■ | | | |
















Feature comparison

| | | | | | | | | | |
|---|--|---|--|---|---|---|---|---|--|
|  | <p>Count contour points Determines the number of contour points within a working area.</p> |  |  | ■ | ■ | ■ | ■ | | |
|  | <p>Contour comparison Compares the contour of a taught-in part with the contour of the current part.</p> |  |  | ■ | ■ | ■ | ■ | ■ | |
|  | <p>Color identification Identifies color within the operating range and its deviation from the reference color.</p> |  |  | ■ | ■ | | | | |
|  | <p>Brightness Determines the average brightness in a working area.</p> |  |  | ■ | ■ | ■ | ■ | | |
|  | <p>Contrast Calculates the contrast in a working area.</p> |  |  | ■ | ■ | ■ | | | |

Models

| | | | | | |
|-----------------------------|-----------------------------|---------------|-------|-------|-------|
| XF700 / XC700 ¹⁾ | XF800 / XC800 ¹⁾ | XF900 / XC900 | CS100 | ID510 | ID100 |
|-----------------------------|-----------------------------|---------------|-------|-------|-------|

Feature comparison

| | | | | | | | | |
|---|---|--|---|---|---|---|--|--|
|  <p>Area size Identifies light or dark respectively color-defined areas in the image. Determines the total area or the largest continuous area.</p> |  |  | ■ | ■ | ■ | | | |
|  <p>Count areas Counts the visible continuous light or dark respectively color-defined areas in the image.</p> |  |  | ■ | ■ | ■ | | | |
|  <p>Pattern comparison Compares the working area with a taught-in pattern.</p> |  |  | ■ | ■ | ■ | | | |
|  <p>Find object positions Finds several objects based on a taught one.</p> |  |  | ■ | M | ■ | M | | |
|  <p>Color positioning Verifies presence of defined colors within defined image sections.</p> |  |  | ■ | ■ | | | | |

Identification

| | | | | | | | | |
|---|---|--|---|---|--|--|---|---|
|  <p>Barcode Reads barcodes. Determines quality according to ISO/IEC 15416, result is output via process interface, can be compared to a set value.</p> |  |  | ■ | ■ | | | ■ | ■ |
|  <p>Matrix code Reads matrix codes (ECC200, GS1, QR, PDF417) at any angle of rotation. Determines quality according to ISO/IEC 15415 or AIM DPM-1-2006, result is output via process interface, can be compared to a set value.</p> |  |  | ■ | ■ | | | ■ | ■ |
|  <p>Text Reads numbers and characters. Characters read are output via process interface, can be compared to a set value.</p> |  |  | ■ | ■ | | | ■ | |

¹⁾ Feature checks available: "M" corresponds to "monochrome sensors only"

Additional features to solve your application.

Image acquisition

| | |
|---|--|
| Optics XF / CS / ID series: | 8 mm 10 mm 12 mm 16 mm |
| Optics XC series: | C-mount |
| Illumination XF / CS / ID series: | White Infrared |
| Illumination XC series: | VeriFlash® (integrated flash controller) |
| <small>(infrared: integrated daylight filter 780 nm)</small> | |
| Configurable web interface: | HTTP HTTPS |
| <small>(live image, job switching, retrieving defect images, MultiViewer (700/800/900))</small> | |
| Save images via: | FTP SFTP |
| Configuration via Ethernet | |

Functions

| | |
|---|--|
| Process linkage: | Digital I/Os |
| Process interface for: | Data output Universal Robots (URCap) |
| Universal Robots+ Certified (UR+) | |
| Ethernet (TCP/IP, UDP) Industrial Ethernet (PROFINET, EtherNet/IP™) RS485 | |
| Baumer FEX® image processor | |
| ColorFEX® intelligent 3D color assistant (device dependent) | |
| User administration / Password protection | |
| Coordinate conversion Automated coordinate alignment via SmartGrid | |
| Distortion correction (monochrome only) Z calibration | |

Process integration

| |
|---|
| Flexible result conjunction |
| Result conjunction with integrated digital inputs |
| Test functionality |
| High-speed mode (monochrome only) |
| Gamma correction (monochrome only) |

¹⁾ non-configurable, Industrial Ethernet not supported

■ Wide range of interfaces

Up to 5 digital inputs and outputs, process interface (device dependent) for result output and/or device control or encoder interface for path-based triggering and ejection – VeriSens® is prepared for almost any integration method. Prefabricated function blocks are available for the Siemens SIMATIC® S7.

■ Integrated FTP/SFTP client

To store live and defect images for tracking or later analysis and / or visualization as easily as possible, all VeriSens® vision sensors support FTP servers.

■ Remote access

The Ethernet interface integrated in all models allows remote access (including gateway and NAT support) via the VeriSens® Application Suite to enable worldwide product access.

| | | | | | | | |
|--------|----------------|---------------|-------|-------|-------|-------|-------|
| Models | XF700 / XFE800 | XC700 / XC800 | XF900 | XC900 | CS100 | ID510 | ID100 |
|--------|----------------|---------------|-------|-------|-------|-------|-------|

| | | | | | | |
|---------------|---------------|---------------|---------------|---------------|---------------|---------------|
| ■ - ■ ■ | - - - - | ■ - ■ - | - - - - | - ■ - ■ | - - ■ - | - ■ - ■ |
| - | ■ | - | ■ | - | - | - |
| ■ ■ | - - | ■ ■ | - - | ■ ■ | ■ ■ | ■ - |
| - | ■ | - | ■ | - | - | - |
| ■ ■ | ■ ■ | ■ ■ | ■ ■ | ■ - | ■ ■ | ■ - |
| ■ | ■ | ■ | ■ | ■ | ■ | ■ |

| | | | | | | |
|-----------|-----------|-----------|-----------|-----------|-----------|---------------------|
| 5 / 5 | 5 / 5 | 5 / 5 | 5 / 5 | 5 / 5 | 5 / 5 | 5 / 3 |
| ■ - | ■ - | - ■ | - ■ | - - | ■ - | ■ ¹⁾ - |
| | | ■ | ■ | | | |
| ■ ■ - | ■ ■ - | ■ ■ - | ■ ■ - | - - - | ■ ■ - | ■ - ■ |
| ■ | ■ | ■ | ■ | ■ | ■ | |
| ■ | ■ | | | | | |
| ■ | ■ | ■ | ■ | | ■ | ■ |
| ■ - | ■ - | ■ ■ | ■ ■ | | | |
| ■ - | ■ - | ■ ■ | ■ ■ | - - | - - | - - |

| | | | | | | |
|---|---|---|---|---|---|---|
| ■ | ■ | ■ | ■ | | | |
| ■ | ■ | ■ | ■ | | | |
| ■ | ■ | ■ | ■ | ■ | ■ | ■ |
| ■ | ■ | ■ | ■ | | | |
| ■ | ■ | ■ | ■ | | | |

■ Integrated test functionality

VeriSens® vision sensors offer an integrated test function which enables you to have images collected during a test run sorted according to good and reject parts in order to evaluate the reliability of the inspection task you created. The test function includes further useful features – ranging from statistical data processing including histogram representation to data export (CSV format).

■ User management

VeriSens® vision sensors feature an integrated user management with password protection, for example, to prevent modification of device settings by machine operators.

■ Backup & Restore Funktion

All VeriSens® vision sensors support service and commissioning through a backup & restore function for the device software settings and inspection tasks stored in the device, to enable easy backup or transmission of this data to other devices.

Worldwide presence.



Africa
Algeria
Cameroon
Côte d'Ivoire
Egypt
Morocco
Reunion
South Africa

America
Brazil
Canada
Colombia
Mexico
United States
Venezuela

Asia
Bahrain
China
India
Indonesia
Israel
Japan
Kuwait
Malaysia
Oman
Philippines
Qatar
Saudi Arabia
Singapore
South Korea
Taiwan
Thailand
UAE

Europe
Austria
Belgium
Bulgaria
Croatia
Czech Republic
Denmark
Finland
France
Germany
Greece
Hungary
Italy
Malta
Martinique
Netherlands
Norway
Poland
Portugal
Romania
Russia
Serbia
Slovakia
Slovenia
Spain
Sweden
Switzerland
Turkey
United Kingdom

Oceania
Australia
New Zealand



For more information
about our worldwide
locations go to:
www.baumer.com/worldwide



Baumer Group
International Sales
P.O. Box · Hummelstrasse 17 · CH-8501 Frauenfeld
Phone +41 (0)52 728 1122 · Fax +41 (0)52 728 1144
sales@baumer.com · www.baumer.com

Represented by: